



Isotope® ANSI CE CSA BALLISTIC



DIELECTRIC



RUBBER NOSEPIECE



INCLUDES STRAP



ADJUSTABLE TEMPLES

Dielectric

Interchangeable temples and neoprene strap

Temples adjust to three different lengths

Dual frame design features a rubber gasket

Passes MIL-PRF 32432 High Velocity Impact Standards

Passes D3: Droplet and Splash Test when worn with strap

| Part No. | Black Frame |
|----------------|----------------|
| GB9410STM ●●●● | AF Clear H2MAX |
| GB9420STM ●●●● | AF Gray H2MAX |
| GB9430STM ●●●● | AF Amber H2MAX |
| GB9480ST ●●●● | AF I/O Mirror |



Watch the video

vimeo.com/pyramex/isotope



Download a FREE QR Reader to your smartphone through your phone's app store

Scan the code

There's more to see at **PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●), or Ballistic (MIL-PRF-32432) (●) standards.



Isotope®

General Specifications

Weight: 41 gm spectacle | 40.68 gm goggle
 PD: 64 mm
 Bridge: 11.7 mm
 Lens base: 9.5 curve
 Lens size diagonal: 74.7 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 163 - 173 mm spectacle | 73 mm goggle
 Overall width (hinge - hinge): 134 mm
 Closest point between temple tips: 65 mm
 Closest point between strap holding parts: 137 mm
 Closest point between lens: 13 mm
 Strap Length: 192 mm spectacle | 520 mm goggle

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Gasket: polycarbonate and thermoplastic elastomers (TPE)
 Temple: polycarbonate
 Temple tips: polycarbonate and thermoplastic elastomers (TPE)
 Temple strap: polyester
 Goggle strap: neoprene
 Goggle strap holder: polycarbonate
 Strap takeup loop: nylon
 Sleeve: polycarbonate
 Nosepiece: thermoplastic rubbers (TPR)

| Part No. | Lens Marking | Frame Marking |
|-----------|-----------------|---------------------------------------|
| GB9410STM | P Z87 + U6 | P Z87 + D3 / P c SEI CAN/CSA Z94.3-15 |
| GB9420STM | P Z87 + U6 L2.5 | P Z87 + D3 / P c SEI CAN/CSA Z94.3-15 |
| GB9430STM | P Z87 + U6 | P Z87 + D3 / P c SEI CAN/CSA Z94.3-15 |
| GB9480ST | P Z87 + U6 L1.7 | P Z87 + D3 / P c SEI CAN/CSA Z94.3-15 |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test with strap
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967