




Products > Climbing-Equipment > Stepladders > L6200 Series > L6208 8 ft Type IA Fiberglass Leaning Ladder > L6208



## L6208 8 ft Type IA Fiberglass Leaning Ladder

[Write the first review](#)

Be the first to [ask a question](#).

### Performance Overview

| Style          | Size | Reach Height | Load Capacity |
|----------------|------|--------------|---------------|
| Leaning Ladder | 8 ft | 12 ft        | 300 lb        |

The L6208 Fiberglass 8 ft Leaning Ladder is ideal for the professional. With a duty rating of 300 pounds, it features the LEANSAFE™ ladder top that secures tools and accessories, and is uniquely designed to securely lean against flat wall surfaces, wall corners, poles, and wall studs and perform as a standard stepladder. LEANSAFE™ ladders have a lower rear rail to front rail connection point allowing the user to get closer to the work when in stepladder mode. Leaning a ladder safely requires that the rear rail is latched to the front rail. Werner's patent pending single latch design stays engaged when needed, and is centrally located to easily open and close.

**BUY NOW** ▶

### Features

- LEANSAFE™ Ladder Top with non-marring rubber bumper securely leans against walls, poles, corners, and wall studs, and holds tools to increase productivity
- Dropped rear rail pivot point gets ladder closer to your work
- Color and branding differentiates LEANSAFE™ from standard stepladders
- Rail latch with single action opening and closing locks the rear rail to the front rail to keep the ladder in leaning mode
- Curved footpad on front feet maximize surface contact with the ground in both leaning mode and stepladder mode
- Double riveted slip-resistant TRACTION-TRED® steps
- Back-up plates reinforce all top connectors
- Heavy duty internal spreaders
- Full set of rear horizontals spaced one per foot
- EDGE360™ bracing protects the ladder feet from every angle
- Every rivet backed up by metal, metal plates or washers to protect rails
- 8 ft LEANSAFE™ leaning ladder in stepladder mode has a maximum standing height of 5 ft 9 in and a max reach height of 12 ft
- 8 ft LEANSAFE™ leaning ladder in leaning mode has a maximum standing height of 4 ft 9 in and a max reach height of 11 ft

### Resources

[View L6200 Series Page](#)

[Model L6208 User Guide](#)

[Replacement Parts](#)

[Share](#)

[Email page](#) | [Print this page](#)

### Accessories



**AC11 Stepladder**

### Specifications

| Feature              | Size / Details |
|----------------------|----------------|
| Size                 | 8 ft           |
| Style                | Leaning Ladder |
| Reach Height         | 12 ft          |
| Max. Standing Height | 5 ft 9 in      |
| Number of Steps      | 8              |

## L6208 8 ft Type IA Fiberglass Leaning Ladder

|                              |   |
|------------------------------|---|
| Load Capacity                | 300 lb  |
| Material                     | Fiberglass  |
| Certifications               | ANSI A14.5 (2007); OSHA   |
| Approx. Spread               | 50.25 in  |
| Color of ladder top          | Yellow  |
| Spreader Material            | Steel   |
| Approx. Shipping Weight Lbs. | 29  |
| Approx. Product Weight Lbs.  | 29  |
| Approx. Cu. Ft. Per Unit     | 11.4  |
| Description of Top Features  | Drill holder, tool slots, magnet, 1 gallon paint can holder, 1 quart paint can holder, non-marring rubber riveted pad, fasteners bin, tape measure slot |

## Dimensions

| Feature                | Size     |
|------------------------|----------|
| Front Rails Dimension  | 3.125 in |
| Front Flange Dimension | 1.188 in |
| Rear Rails Dimension   | 1.875 in |
| Rear Flange Dimension  | 1.88 in  |
| Steps Dimension        | 3 in     |

## Additional L6200 Series Models

| Model No.             | Size  | Reach Height | Max. Standing Height | Number of Steps | Approx. Spread | Approx. Shipping Weight Lbs. | Buy Online     |
|-----------------------|-------|--------------|----------------------|-----------------|----------------|------------------------------|----------------|
| <a href="#">L6204</a> | 4 ft  | 8 ft         | 1 ft 8 in            | 4               | 25 in          | 16                           | <b>BUY NOW</b> |
| <a href="#">L6206</a> | 6 ft  | 10 ft        | 3 ft 10 in           | 6               | 38 in          | 21                           | <b>BUY NOW</b> |
| <a href="#">L6208</a> | 8 ft  | 12 ft        | 5 ft 9 in            | 8               | 50.25 in       | 29                           | <b>BUY NOW</b> |
| <a href="#">L6210</a> | 10 ft | 14 ft        | 7 ft 8 in            | 10              | 62.5 in        | 38                           | <b>BUY NOW</b> |
| <a href="#">L6212</a> | 12 ft | 16 ft        | 9 ft 7 in            | 12              | 75 in          | 48                           | <b>BUY NOW</b> |

## Ratings Summary

Be the first to [write a review](#)

## Product Q&A

(0 Questions : 0 Answers)

Be the first to ask a question! [Ask a new question](#)

**PRODUCTS**

Climbing Equipment  
Fall Protection  
Racks & Ramps  
Featured Products

**SUPPORT**

Replacement Parts  
Safety Tips  
FAQ  
Literature  
Where To Buy  
Login

**NEWS & EVENTS**

News Releases  
Featured Videos  
Current Events  
Sponsorships  
Image Library

**COMPANY**

Profile  
Why Werner  
Innovation  
Locations  
Contact Us  
Legal Notices  
MyWernerCo

© 2017 Werner Co. All Rights Reserved.