

# SOCKETS & ACCESSORIES.

## DESIGNED TO INCREASE TORQUE.

The radius corner design of Blackhawk™ by Proto® sockets allows contact with the flat edges of the fastener, not the points. This style of contact moves the driving force from the corners to the flat areas, increasing the torque on the fastener, reducing rounding and increasing safety. Ratchets, sockets and accessories are double-nickel chrome plated for a corrosion resistant, full polish finish.



**Blackhawk**  
BY PROTO

# Sockets & Accessories



## 1/4" DRIVE QUICK RELEASE RATCHET

- Full polish.
- Chrome plated positive grip ratchet.
- 43 tooth design, double pawl.
- 8.4 degrees of arc required for new "bite."
- Works easily in confined areas.
- Knurled speed ring means you can start the fastener without turning the handle.

Item No.	Description	Length	Weight
GW-9955B	Quick Release Ratchet	5.75"	0.31 lbs.

ASME B107.10M



## 1/4" DRIVE ROUND HEAD REVERSIBLE RATCHET

- Chrome plated positive grip ratchet.
- 43 tooth design.
- Works easily in confined areas.
- Knurled speed ring means you can start the fastener without turning the handle.

Item No.	Description	Length	Weight
GW-9945B	43 Tooth	5.80"	0.41 lbs.
GW-9945BR	Ratchet Renewal Kit		

ASME B107.10M



## 1/4" DRIVE FLEX HEAD RATCHET

- Features the same design as our standard ratchet (GW-9945B).
- No grooves or ball bearing to wear out in the hinge.
- Springs in each of the forks of the hinge allow for infinite angles.

Item No.	Description	Length	Weight
GW-9935B	43 Tooth Flex-Head	6.68"	0.38 lbs.
GW-9945BR	Ratchet Renewal Kit		



## 1/4" DRIVE ROTATOR™ RATCHET

- Handle rotates 360° in either direction for rapid "twist-action" nut and fastener application and removal.
- Pear head design.
- Quick-release switch for fast socket removal.

Item No.	Length	Weight
GW-9946R	7.25"	0.50 lbs.

ASME B107.10M



## 1/4" DRIVE FLEX HANDLE

Item No.	Length	Weight
GW-9749B	5.90"	0.24 lbs.

ASME B107.10M



## 1/4" DRIVE EXTENSIONS

Item No.	Length	Weight
GW-9898	3.00"	0.08 lbs.
GW-9899	6.00"	0.16 lbs.

ASME B107.10M



# Sockets & Accessories

## 1/4" DRIVE FLEXIBLE SPINNER

- Flexible shaft permits reaching around obstructions.

Item No.	Length	Weight
GW-9545	6.63"	0.14 lbs.

## 1/4" DRIVE SPINNER HANDLE

Item No.	Length	Weight
GW-9550	6"	0.20 lbs.

ASME B107.10M

## 1/4" DRIVE UNIVERSAL JOINT

Item No.	Length	Weight
GW-9578A	1.25"	0.06 lbs.

ASME B107.10M

## 1/4" DRIVE ADAPTER

Part No.	Female/Male	Length	Weight
34960	1/4" to 3/8"	1.0"	0.04 lbs.

ASME B107.10M

## 1/4" DRIVE SOCKETS — 6 POINT

Item No.	Size	Length	Weight
GW-1605	5/32"	0.8"	0.03 lbs.
GW-1606	3/16"	0.8"	0.03 lbs.
GW-1607	7/32"	0.8"	0.03 lbs.
GW-1608	1/4"	0.8"	0.03 lbs.
GW-1609	9/32"	0.8"	0.03 lbs.
GW-1610	5/16"	0.8"	0.03 lbs.
GW-1611	11/32"	0.8"	0.04 lbs.
GW-1612	3/8"	0.8"	0.04 lbs.
GW-1614	7/16"	0.8"	0.05 lbs.
GW-1616	1/2"	0.8"	0.05 lbs.

ASME B107.1

## 1/4" DRIVE **METRIC** SOCKETS — 6 POINT

Item No.	Size	Length	Weight
GW-604M	4 mm	0.8"	0.02 lbs
GW-645M	4.5 mm	0.8"	0.03 lbs
GW-605M	5 mm	0.8"	0.03 lbs
GW-655M	5.5 mm	0.8"	0.03 lbs
GW-606M	6 mm	0.8"	0.03 lbs
GW-607M	7 mm	0.8"	0.03 lbs
GW-608M	8 mm	0.8"	0.03 lbs
GW-609M	9 mm	0.8"	0.03 lbs
GW-610M	10 mm	0.8"	0.04 lbs
GW-611M	11 mm	0.8"	0.06 lbs
GW-612M	12 mm	0.8"	0.06 lbs
GW-613M	13 mm	0.8"	0.06 lbs

ASME B107.5M



# Sockets & Accessories



## 1/4" DRIVE DEEP SOCKETS — 6 POINT

Item No.	Size	Length	Weight
GW-1506	3/16"	1.9"	0.06 lbs.
GW-1507	7/32"	1.9"	0.06 lbs.
GW-1508	1/4"	1.9"	0.06 lbs.
GW-1509	9/32"	1.9"	0.06 lbs.
GW-1510	5/16"	1.9"	0.06 lbs.
GW-1511	11/32"	1.9"	0.08 lbs.
GW-1512	3/8"	1.9"	0.09 lbs.
GW-1514	7/16"	1.9"	0.10 lbs.
GW-1516	1/2"	1.9"	0.12 lbs.

ASME B107.1M



## 1/4" DRIVE DEEP **METRIC** SOCKETS — 6 POINT

Item No.	Size	Length	Weight
GW-504M	4 mm	1.9"	0.05 lbs.
GW-505M	5 mm	1.9"	0.06 lbs.
GW-506M	6 mm	1.9"	0.06 lbs.
GW-507M	7 mm	1.9"	0.06 lbs.
GW-508M	8 mm	1.9"	0.06 lbs.
GW-509M	9 mm	1.9"	0.07 lbs.
GW-510M	10 mm	1.9"	0.09 lbs.
GW-511M	11 mm	1.9"	0.10 lbs.
GW-512M	12 mm	1.9"	0.11 lbs.
GW-513M	13 mm	1.9"	0.11 lbs.

ASME B107.5M



## 1/4" DRIVE SOCKETS — 8 POINT

Item No.	Size	Length	Weight
GW-1208	1/4"	0.8"	0.02 lbs.
GW-1210	5/16"	0.8"	0.04 lbs.
GW-1212	3/8"	0.8"	0.06 lbs.

ASME B107.1



## 1/4" DRIVE SOCKETS — 12 POINT

Item No.	Size	Length	Weight
GW-1705	5/32"	0.8"	0.02 lbs.
GW-1706	3/16"	0.8"	0.03 lbs.
GW-1707	7/32"	0.8"	0.03 lbs.
GW-1708	1/4"	0.8"	0.03 lbs.
GW-1709	9/32"	0.8"	0.03 lbs.
GW-1710	5/16"	0.8"	0.04 lbs.
GW-1711	11/32"	0.8"	0.04 lbs.
GW-1712	3/8"	0.8"	0.05 lbs.
GW-1714	7/16"	0.8"	0.05 lbs.
GW-1716	1/2"	0.8"	0.06 lbs.

ASME B107.1



## 1/4" DRIVE **METRIC** SOCKETS — 12 POINT

Item No.	Size	Length	Weight
GW-705M	5 mm	0.8"	0.01 lbs.
GW-755M	5.5 mm	0.8"	0.02 lbs.
GW-706M	6 mm	0.8"	0.02 lbs.
GW-707M	7 mm	0.8"	0.02 lbs.
GW-708M	8 mm	0.8"	0.02 lbs.
GW-709M	9 mm	0.8"	0.03 lbs.
GW-710M	10 mm	0.8"	0.04 lbs.
GW-711M	11 mm	0.8"	0.05 lbs.
GW-712M	12 mm	0.8"	0.05 lbs.
GW-713M	13 mm	0.8"	0.06 lbs.

ASME B107.5M



# Sockets & Accessories

## 1/4" DRIVE DEEP SOCKETS — 12 POINT

Item No.	Size	Length	Weight
GW-1406	3/16"	1.9"	0.02 lbs.
GW-1407	7/32"	1.9"	0.02 lbs.
GW-1408	1/4"	1.9"	0.02 lbs.
GW-1409	9/32"	1.9"	0.02 lbs.
GW-1410	5/16"	1.9"	0.02 lbs.
GW-1411	11/32"	1.9"	0.02 lbs.
GW-1412	3/8"	1.9"	0.03 lbs.
GW-1414	7/16"	1.9"	0.03 lbs.
GW-1416	1/2"	1.9"	0.04 lbs.

ASME B107.1

## 1/4" DRIVE DEEP **METRIC** SOCKETS — 12 POINT

Item No.	Size	Length	Weight
GW-1605M	5 mm	1.9"	0.07 lbs
GW-1606M	6 mm	1.9"	0.09 lbs
GW-1607M	7 mm	1.9"	0.09 lbs
GW-1608M	8 mm	1.9"	0.15 lbs
GW-1609M	9 mm	1.9"	0.06 lbs.
GW-1610M	10 mm	1.9"	0.04 lbs.
GW-1611M	11 mm	1.9"	0.04 lbs.
GW-1612M	12 mm	1.9"	0.10 lbs.
GW-1613M	13 mm	1.9"	0.11 lbs.

ASME B107.5M

## 1/4" DRIVE TORX® SOCKETS INTERNAL

Item No.	Size	Weight
TS-1209	T9	0.02 lbs.
TS-1210	T10	0.02 lbs.
TS-1215	T15	0.02 lbs.
TS-1220	T20	0.03 lbs.
TS-1225	T25	0.03 lbs.
TS-1227	T27	0.03 lbs.
TS-1230	T30	0.04 lbs.

## 1/4" DRIVE TAMPER-RESISTANT TORX® SOCKETS INTERNAL

Item No.	Size	Weight
TR-3210	T10	0.03 lbs.
TR-3215	T15	0.03 lbs.
TR-3220	T20	0.03 lbs.
TR-3225	T25	0.04 lbs.
TR-3227	T27	0.04 lbs.
TR-3230	T30	0.04 lbs.

## 1/4" DRIVE TORX® SOCKETS EXTERNAL

Item No.	Size	Weight
TS-2204	E4	0.04 lbs.
TS-2205	E5	0.04 lbs.
TS-2206	E6	0.04 lbs.
TS-2207	E7	0.04 lbs.
TS-2208	E8	0.04 lbs.

## 1/4" DRIVE HEX BIT HOLDER

Item No.	Size	Weight
9000H	1/4"	0.05 lbs.



# Sockets & Accessories



## 3/8" DRIVE QUICK RELEASE RATCHET

- Full polish.
- Chrome plated positive grip ratchet.
- 41 tooth design, double pawl.
- 8.8 degrees of arc required for new "bite."
- Works easily in confined areas.
- Knurled speed ring means you can start the fastener without turning the handle.

Item No.	Description	Length	Weight
34946B	41 Tooth Double Pawl	7.9"	0.76 lbs.
34946BR	Ratchet Renewal Kit		0.20 lbs.

ASME B107.10M



## 3/8" DRIVE ROUND HEAD REVERSIBLE RATCHET

- Chrome plated positive grip ratchet.
- 41 tooth design.
- Works easily in confined areas.
- Knurled speed ring means you can start the fastener without turning the handle.

Item No.	Description	Length	Weight
34945B	41 Tooth	7.9"	0.79 lbs.
34945BR	Ratchet Renewal Kit		0.23 lbs.

ASME B107.10M



## 3/8" DRIVE INDEXIBLE HEAD RATCHET

- Full polish.
- Chrome plated positive grip ratchet.
- 5-position adjustable head allows the user to maneuver around obstructions and allows access to hard-to-reach fasteners.
- Head rotates 360° in the unlocked position to "speed" the fastener on or off.
- Quick release feature holds sockets securely and releases them on demand.

Item No.	Description	Length	Weight
34950X	60 Tooth	10"	0.99 lbs.



## 3/8" DRIVE BENT HANDLE FLEX-HEAD RATCHET

Item No.	Description	Length	Weight
34947B	41 Tooth	10.9"	1.01 lbs.
34945BR	Ratchet Renewal Kit		0.23 lbs.

## 3/8" DRIVE FLEX-HEAD RATCHET

- Same head design as the 34945B.
- No grooves or ball bearing to wear out in the hinge.
- Springs in each of the forks of the hinge allow for infinite angles.

Item No.	Description	Length	Weight
34935B	41 Tooth	11"	0.98 lbs.
34945BR	Ratchet Renewal Kit		0.23 lbs.



# Sockets & Accessories

## 3/8" DRIVE MINI FLEX RATCHET

- This compact flex head ratchet allows you to reach places inaccessible to standard ratchets.
- Head design is the same as the 34945B.

Item No.	Description	Length	Weight
34948B	41 Tooth	5.9"	0.62 lbs.
34945BR	Ratchet Renewal Kit		0.23 lbs.



## 3/8" DRIVE ROTATOR™ RATCHET

- Handle rotates 360° in either direction for rapid "twist-action" nut and fastener application and removal.
- Pear head design.
- Quick-release switch for fast socket removal.

Item No.	Length	Weight
34950R	8.8"	1.0 lbs.

ASME B107.10M



## 3/8" DRIVE FLEX HANDLE

Item No.	Length	Weight
34986B	9.8"	0.67 lbs.

ASME B107.10M



## 3/8" DRIVE SPEEDER HANDLE

Item No.	Length	Weight
34982	15.5"	0.92 lbs.

ASME B107.10M



## 3/8" DRIVE EXTENSIONS

Item No.	Length	Weight
34989	1.7"	0.10 lbs.
34988	3.0"	0.16 lbs.
34987	6.0"	0.32 lbs.
34984	12.0"	0.63 lbs.
34983	20.0"	1.07 lbs.

ASME B107.10M



## 3/8" DRIVE UNIVERSAL JOINT

Item No.	Description	Length	Weight
34993A	Universal Joint	1.9"	0.14 lbs.

ASME B107.10M



# Sockets & Accessories



## 3/8" DRIVE ADAPTERS

Item No.	Female/Male	Length	Weight
34963	3/8" to 1/4"	0.60"	0.06 lbs.
34966	3/8" to 1/2"	1.40"	0.10 lbs.

ASME B107.10M



## 3/8" DRIVE SPARK PLUG SOCKETS — 6 POINT

- Rubber insert included to help grip socket plug and reduce breakage.

Item No.	Opening	Weight
HW-1520S	5/8"	0.22 lbs.
HW-1526S	13/16"	0.33 lbs.

ASME B107.34M



## 3/8" DRIVE UNIVERSAL SPARK PLUG SOCKETS — 6 POINT

- Rubber insert included to help grip socket plug and reduce breakage.

Item No.	Size	Length	Weight
30320S	5/8"	3.3"	0.26 lbs.
30326	13/16"	3.5"	0.41 lbs.

ASME B107.34M



## 3/8" DRIVE UNIVERSAL SOCKETS — 6 POINT

Item No.	Size	Length	Weight
30212	3/8"	1.7"	0.12 lbs.
30214	7/16"	1.8"	0.13 lbs.
30216	1/2"	1.8"	0.14 lbs.
30218	9/16"	1.8"	0.14 lbs.
30220	5/8"	1.9"	0.15 lbs.
30222	11/16"	1.9"	0.17 lbs.
30224	3/4"	2.0"	0.18 lbs.

ASME B107.1



## 3/8" DRIVE **METRIC** UNIVERSAL SOCKETS — 6 POINT

Item No.	Size	Length	Weight
30209M	9 mm	1.7"	0.12 lbs.
30210M	10 mm	1.8"	0.13 lbs.
30211M	11 mm	1.8"	0.14 lbs.
30212M	12 mm	1.8"	0.14 lbs.
30213M	13 mm	1.9"	0.14 lbs.
30214M	14 mm	1.9"	0.14 lbs.
30215M	15 mm	2.0"	0.15 lbs.

ASME B107.5M





# Sockets & Accessories

## 3/8" DRIVE SOCKETS — 6 POINT

Item No.	Size	Length	Weight
30608	1/4"	0.9"	0.05 lbs.
30010	5/16"	0.9"	0.05 lbs.
30612	3/8"	0.9"	0.05 lbs.
30614	7/16"	0.9"	0.05 lbs.
30616	1/2"	1.0"	0.07 lbs.
30618	9/16"	1.0"	0.08 lbs.
30620	5/8"	1.0"	0.10 lbs.
30622	11/16"	1.0"	0.10 lbs.
30624	3/4"	1.1"	0.13 lbs.
30626	13/16"	1.2"	0.15 lbs.
30628	7/8"	1.2"	0.20 lbs.
30630	15/16"	1.2"	0.22 lbs.
30632	1"	1.4"	0.27 lbs.

ASME B107.1



## 3/8" DRIVE METRIC SOCKETS — 6 POINT

Item No.	Size	Length	Weight
32007M	7 mm	0.9"	0.05 lbs.
32008M	8 mm	0.9"	0.05 lbs.
32009M	9 mm	0.9"	0.05 lbs.
32010M	10 mm	0.9"	0.05 lbs.
32011M	11 mm	0.9"	0.06 lbs.
32012M	12 mm	1.0"	0.06 lbs.
32013M	13 mm	1.0"	0.07 lbs.
32014M	14 mm	1.0"	0.08 lbs.
32015M	15 mm	1.0"	0.09 lbs.
32016M	16 mm	1.0"	0.10 lbs.
32017M	17 mm	1.0"	0.12 lbs.
32018M	18 mm	1.1"	0.13 lbs.
32019M	19 mm	1.1"	0.14 lbs.
32020M	20 mm	1.2"	0.18 lbs.
32021M	21 mm	1.2"	0.17 lbs.
32022M	22 mm	1.2"	0.21 lbs.

ASME B107.5M



## 3/8" DRIVE SOCKETS — 8 POINT

Item No.	Size	Length	Weight
31108	1/4"	0.9"	0.06 lbs.
31110	5/16"	0.9"	0.06 lbs.
31112	3/8"	0.9"	0.07 lbs.
31114	7/16"	0.9"	0.10 lbs.
31116	1/2"	1.0"	0.11 lbs.

ASME B107.1



## 3/8" DRIVE SOCKETS — 12 POINT

Item No.	Size	Length	Weight
30010A	5/16"	0.9"	0.05 lbs.
30012	3/8"	0.9"	0.05 lbs.
30014	7/16"	0.9"	0.05 lbs.
30016	1/2"	0.9"	0.07 lbs.
30018	9/16"	1.0"	0.09 lbs.
30020	5/8"	1.0"	0.09 lbs.
30022	11/16"	1.0"	0.10 lbs.
30024	3/4"	1.1"	0.14 lbs.
30026	13/16"	1.2"	0.15 lbs.
30028	7/8"	1.2"	0.19 lbs.
300301	15/16"	1.2"	0.30 lbs.
300321	1"	1.4"	0.32 lbs.

ASME B107.1



# Sockets & Accessories



## 3/8" DRIVE **METRIC** SOCKETS — 12 POINT

Item No.	Size	Length	Weight
34007M	7 mm	0.9"	0.05 lbs.
34008M	8 mm	0.9"	0.05 lbs.
34009M	9 mm	0.9"	0.06 lbs.
34010M	10 mm	0.9"	0.06 lbs.
34011M	11 mm	0.9"	0.06 lbs.
34012M	12 mm	1.0"	0.06 lbs.
34013M	13 mm	1.0"	0.08 lbs.
34014M	14 mm	1.0"	0.08 lbs.
34015M	15 mm	1.0"	0.10 lbs.
34016M	16 mm	1.0"	0.10 lbs.
34017M	17 mm	1.0"	0.13 lbs.
34018M	18 mm	1.1"	0.14 lbs.
34019M	19 mm	1.1"	0.14 lbs.
34020M	20 mm	1.2"	0.17 lbs.
34021M	21 mm	1.2"	0.18 lbs.
34022M	22 mm	1.2"	0.21 lbs.

ASME B107.5M



## 3/8" DRIVE DEEP SOCKETS — 6 POINT

Item No.	Size	Length	Weight
HW-1510	5/16"	1.8"	0.09 lbs.
HW-1512	3/8"	1.8"	0.09 lbs.
HW-1514	7/16"	1.8"	0.10 lbs.
HW-1516	1/2"	1.8"	0.12 lbs.
HW-1518	9/16"	2.0"	0.18 lbs.
HW-1520	5/8"	2.1"	0.20 lbs.
HW-1522	11/16"	2.2"	0.24 lbs.
HW-1524	3/4"	2.2"	0.27 lbs.
HW-1526	13/16"	2.5"	0.33 lbs.
HW-1528	7/8"	2.5"	0.40 lbs.
HW-1530	15/16"	2.8"	0.50 lbs.
HW-1532	1"	2.8"	0.56 lbs.

ASME B107.1



## 3/8" DRIVE **METRIC** DEEP SOCKETS — 6 POINT

Item No.	Size	Length	Weight
HW-1507M	7 mm	2.1"	0.10 lbs.
HW-1508M	8 mm	2.1"	0.10 lbs.
HW-1509M	9 mm	2.1"	0.11 lbs.
HW-1510M	10 mm	1.8"	0.11 lbs.
HW-1511M	11 mm	1.8"	0.11 lbs.
HW-1512M	12 mm	1.8"	0.12 lbs.
HW-1513M	13 mm	1.8"	0.13 lbs.
HW-1514M	14 mm	2.0"	0.16 lbs.
HW-1515M	15 mm	2.1"	0.21 lbs.
HW-1517M	17 mm	2.2"	0.22 lbs.
HW-1518M	18 mm	2.2"	0.22 lbs.
HW-1519M	19 mm	2.2"	0.33 lbs.

ASME B107.5M



# Sockets & Accessories

## 3/8" DRIVE DEEP SOCKETS — 12 POINT

Item No.	Size	Length	Weight
30412	3/8"	1.8"	0.09 lbs.
30414	7/16"	1.8"	0.09 lbs.
30416	1/2"	1.8"	0.12 lbs.
30418	9/16"	2.0"	0.16 lbs.
30420	5/8"	2.1"	0.18 lbs.
30422	11/16"	2.2"	0.23 lbs.
30424	3/4"	2.2"	0.25 lbs.
30426	13/16"	2.5"	0.32 lbs.
30428	7/8"	2.5"	0.38 lbs.
30430	15/16"	2.5"	0.47 lbs.
30432	1"	2.5"	0.52 lbs.

ASME B107.1



## 3/8" DRIVE **METRIC** DEEP SOCKETS — 12 POINT

Item No.	Size	Length	Weight
HW-1607M	7 mm	2.1"	0.10 lbs.
HW-1608M	8 mm	2.1"	0.10 lbs.
HW-1609M	9 mm	2.1"	0.11 lbs.
HW-1610M	10 mm	1.8"	0.11 lbs.
HW-1611M	11 mm	1.8"	0.12 lbs.
HW-1612M	12 mm	1.8"	0.12 lbs.
HW-1613M	13 mm	1.8"	0.16 lbs.
HW-1614M	14 mm	1.8"	0.16 lbs.
HW-1615M	15 mm	2.8"	0.24 lbs.
HW-1616M	16 mm	2.8"	0.24 lbs.
HW-1617M	17 mm	2.8"	0.27 lbs.
HW-1618M	18 mm	2.8"	0.27 lbs.
HW-1619M	19 mm	2.8"	0.31 lbs.

ASME B107.5M



## 3/8" DRIVE CROWFOOT

• Satin Finish.

Item No.	Size	Length	Weight
BCF-12	3/8"	1.2"	0.06 lbs.
BCF-14	7/16"	1.2"	0.06 lbs.
BCF-16	1/2"	1.4"	0.07 lbs.
BCF-18	9/16"	1.4"	0.08 lbs.
BCF-20	5/8"	1.6"	0.09 lbs.
BCF-22	11/16"	1.6"	0.10 lbs.
BCF-24	3/4"	1.7"	0.11 lbs.
BCF-26	13/16"	1.7"	0.11 lbs.
BCF-28	7/8"	1.8"	0.12 lbs.
BCF-32	1"	1.8"	0.14 lbs.

ASME B107.21



# Sockets & Accessories



## 3/8" DRIVE CROWFOOT – METRIC

• Satin Finish.

Item No.	Size	Length	Weight
BCF-10M	10 mm	1.2"	0.06 lbs.
BCF-11M	11 mm	1.2"	0.07 lbs.
BCF-12M	12 mm	1.4"	0.07 lbs.
BCF-13M	13 mm	1.4"	0.07 lbs.
BCF-14M	14 mm	1.4"	0.09 lbs.
BCF-15M	15 mm	1.6"	0.09 lbs.
BCF-16M	16 mm	1.6"	0.09 lbs.
BCF-17M	17 mm	1.6"	0.09 lbs.
BCF-19M	19 mm	1.7"	0.11 lbs.
BCF-21M	21 mm	1.7"	0.11 lbs.
BCF-22M	22 mm	1.7"	0.12 lbs.

ASME 107.21



## 3/8" DRIVE SLOTTED SCREWDRIVER BITS

Item No.	Description	Length	Weight
HW-9504	3/16" Wide Tip	2"	0.10 lbs.
HW-9505	1/4" Wide Tip	2"	0.10 lbs.
HW-9506	5/16" Wide Tip	2"	0.11 lbs.



## 3/8" DRIVE PHILLIPS® SCREWDRIVER BITS

Item No.	Size	Weight
HW-9450	No. 1	0.09 lbs.
HW-9451	No. 2	0.10 lbs.
HW-9452	No. 3	0.10 lbs.
HW-9453	No. 4	0.10 lbs.

Phillips® is a registered trademark of Phillips Screw Co.  
Torx® is a registered trademark of Acument Intellectual Properties, LLC



# Sockets & Accessories

## 3/8" DRIVE TORX® SOCKETS INTERNAL

Item No.	Size	Weight
TS-1340	T40	0.07 lbs.
TS-1345	T45	0.08 lbs.
TS-1347	T47	0.08 lbs.
TS-1350	T50	0.09 lbs.
TS-1355	T55	0.11 lbs.



## 3/8" DRIVE TAMPER-RESISTANT TORX® SOCKETS INTERNAL

Item No.	Size	Weight
TR-3340	T40	0.08 lbs.
TR-3345	T45	0.09 lbs.
TR-3350	T50	0.10 lbs.



## 3/8" DRIVE TORX® SOCKETS EXTERNAL

Item No.	Size	Weight
TS-2308	E8	0.06 lbs.
TS-2310	E10	0.08 lbs.
TS-2312	E12	0.08 lbs.
TS-2314	E14	0.09 lbs.
TS-2316	E16	0.12 lbs.



# Sockets & Accessories



## 3/8" DRIVE HEX BIT SOCKETS

Item No.	Size	Length	Weight
HW-9442	1/8"	2.0"	0.10 lbs.
HW-9443	9/64"	2.0"	0.10 lbs.
HW-9444	5/32"	2.0"	0.11 lbs.
HW-9449	3/16"	2.0"	0.11 lbs.
HW-9448	7/32"	2.0"	0.11 lbs.
HW-9447	1/4"	2.0"	0.11 lbs.
HW-9446	5/16"	2.0"	0.11 lbs.
HW-9445	3/8"	2.0"	0.13 lbs.



## 3/8" DRIVE *METRIC* HEX BIT SOCKETS

Item No.	Size	Length	Weight
HW-9404M	4 mm	2.0"	0.10 lbs.
HW-9405M	5 mm	2.0"	0.11 lbs.
HW-9406M	6 mm	2.0"	0.11 lbs.
HW-9407M	7 mm	2.0"	0.11 lbs.
HW-9408M	8 mm	2.0"	0.11 lbs.
HW-9410M	10 mm	2.0"	0.12 lbs.



## 3/8" DRIVE IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
U-1508	1/4"	1.1"	0.08 lbs.
U-1510	5/16"	1.1"	0.09 lbs.
U-1512	3/8"	1.1"	0.09 lbs.
U-1514	7/16"	1.1"	0.09 lbs.
U-1516	1/2"	1.1"	0.09 lbs.
U-1518	9/16"	1.1"	0.11 lbs.
U-1520	5/8"	1.1"	0.14 lbs.
U-1522	11/16"	1.1"	0.17 lbs.
U-1524	3/4"	1.1"	0.17 lbs.

ASME B107.2



# Sockets & Accessories

## 3/8" DRIVE **METRIC** IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
U-1508M	8 mm	1.0"	0.07 lbs.
U-1509M	9 mm	1.0"	0.04 lbs.
U-1510M	10 mm	1.0"	0.05 lbs.
U-1512M	12 mm	1.1"	0.09 lbs.
U-1513M	13 mm	1.1"	0.10 lbs.
U-1514M	14 mm	1.1"	0.11 lbs.
U-1515M	15 mm	1.1"	0.12 lbs.
U-1517M	17 mm	1.1"	0.16 lbs.
U-1518M	18 mm	1.1"	0.18 lbs.
U-1519M	19 mm	1.1"	0.19 lbs.

ASME B107.33M



## 3/8" DRIVE DEEP IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
U-1610	5/16"	2.8"	0.20 lbs.
U-1612	3/8"	2.8"	0.20 lbs.
U-1614	7/16"	2.8"	0.18 lbs.
U-1616	1/2"	2.8"	0.20 lbs.
U-1618	9/16"	2.8"	0.24 lbs.
U-1620	5/8"	2.8"	0.30 lbs.
U-1622	11/16"	2.8"	0.37 lbs.
U-1624	3/4"	2.8"	0.38 lbs.

ASME B107.2



## 3/8" DRIVE **METRIC** DEEP IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
U-1608M	8 mm	2.8"	0.20 lbs.
U-1609M	9 mm	2.8"	0.21 lbs.
U-1610M	10 mm	2.8"	0.20 lbs.
U-1611M	11 mm	2.8"	0.18 lbs.
U-1612M	12 mm	2.8"	0.21 lbs.
U-1613M	13 mm	2.8"	0.21 lbs.
U-1614M	14 mm	2.8"	0.27 lbs.
U-1615M	15 mm	2.8"	0.27 lbs.
U-1616M	16 mm	2.8"	0.29 lbs.
U-1617M	17 mm	2.8"	0.37 lbs.
U-1618M	18 mm	2.8"	0.39 lbs.
U-1619M	19 mm	2.8"	0.39 lbs.

ASME B107.33M



# Sockets & Accessories



## 1/2" DRIVE QUICK RELEASE RATCHET

- Full polish.
- Chrome plated positive grip ratchet.
- 45 tooth design, double pawl.
- 8.0 degrees of arc required for new "bite."
- Works easily in confined areas.
- Knurled speed ring means you can start the fastener without turning the handle.

Item No.	Description	Length	Weight
49946B	45 Tooth Double Pawl	10.1"	1.22 lbs.
49946BR	Ratchet Renewal Kit		0.33 lbs.

ASME B107.10M



## 1/2" DRIVE ROUND HEAD REVERSIBLE RATCHET

- Chrome plated positive grip ratchet.
- 45 tooth design.
- Works easily in confined areas.
- Knurled speed ring means you can start the fastener without turning the handle.

Item No.	Description	Length	Weight
49945B	45 Tooth	10.1"	1.34 lbs.
49945BR	Ratchet Renewal Kit		0.37 lbs.

ASME B107.10M



## 1/2" DRIVE FLEX HANDLE

Item No.	Length	Weight
49988B	17.2"	1.76 lbs.

ASME B107.10M



## 1/2" DRIVE SPEEDER

Item No.	Length	Weight
49992	18.2"	1.76 lbs.

ASME B107.10M



## 1/2" DRIVE EXTENSIONS

Item No.	Length	Weight
49964	2"	0.21 lbs.
49966	5"	0.46 lbs.
49990	10"	0.90 lbs.
49972	19"	1.92 lbs.

ASME B107.10M



## 1/2" DRIVE ADAPTERS

Item No.	Female/Male	Length	Weight
34965	1/2" to 3/8"	1.3"	0.13 lbs.
69992	1/2" to 3/4"	1.7"	0.25 lbs.

ASME B107.10M





# Sockets & Accessories

## 1/2" DRIVE UNIVERSAL JOINT

Item No.	Length	Weight
49978A	2.7"	0.29 lbs.

ASME B107.10M

## 1/2" DRIVE DRAG LINK SOCKET

- A sturdy screwdriver type socket with bit for drag links, drain plugs, slotted nuts and screws.
- Will fit any standard 1/2" square drive tool.

Item No.	Length	Weight
49979	0.94" wide	0.18 lbs.

## 1/2" DRIVE SPARK PLUG SOCKETS — 6 POINT

- Rubber insert included to help grip socket plug and reduce breakage.

Item No.	Size	Length	Weight
40326S	13/16"	2.7"	0.36 lbs.
40320S	5/8"	2.5"	0.22 lbs.

ASME B107.34M

## 1/2" DRIVE SOCKETS — 6 POINT

Item No.	Size	Length	Weight
40612	3/8"	1.5"	0.10 lbs.
40614	7/16"	1.5"	0.11 lbs.
40616	1/2"	1.5"	0.13 lbs.
40618	9/16"	1.5"	0.14 lbs.
40620	5/8"	1.5"	0.14 lbs.
40622	11/16"	1.5"	0.19 lbs.
40624	3/4"	1.5"	0.19 lbs.
40626	13/16"	1.5"	0.19 lbs.
40628	7/8"	1.5"	0.24 lbs.
40630	15/16"	1.5"	0.26 lbs.
40632	1"	1.6"	0.30 lbs.
40634	1-1/16"	1.7"	0.35 lbs.
40636	1-1/8"	1.7"	0.42 lbs.
40640	1-1/4"	1.8"	0.48 lbs.
40642A	1-1/2"	2.3"	1.12 lbs.

ASME B107.1

## 1/2" DRIVE **METRIC** SOCKETS — 6 & 12 POINT

Item No.	Size	Length	Weight	Pt.
43010M	10 mm	1.5"	0.11 lbs.	12 PT
43011M	11 mm	1.5"	0.11 lbs.	12 PT
43012M	12 mm	1.5"	0.12 lbs.	12 PT
43013M	13 mm	1.5"	0.12 lbs.	12 PT
43014M	14 mm	1.5"	0.14 lbs.	12 PT
43015M	15 mm	1.5"	0.16 lbs.	6 PT
43017M	17 mm	1.5"	0.16 lbs.	6 PT
43019M	19 mm	1.5"	0.20 lbs.	6 PT
43021M	21 mm	1.5"	0.21 lbs.	6 PT
43022M	22 mm	1.5"	0.25 lbs.	6 PT
43023M	23 mm	1.5"	0.26 lbs.	6 PT
43024M	24 mm	1.5"	0.31 lbs.	6 PT
43027M	27 mm	1.7"	0.44 lbs.	6 PT

ASME B107.5M



# Sockets & Accessories



## 1/2" DRIVE SOCKETS — 12 POINT

Item No.	Size	Length	Weight
40112	3/8"	1.5"	0.11 lbs.
40114	7/16"	1.5"	0.11 lbs.
40116	1/2"	1.5"	0.12 lbs.
40118	9/16"	1.5"	0.12 lbs.
40120	5/8"	1.5"	0.12 lbs.
40122	11/16"	1.5"	0.16 lbs.
40124	3/4"	1.5"	0.16 lbs.
40126	13/16"	1.5"	0.18 lbs.
40128	7/8"	1.5"	0.22 lbs.
40130	15/16"	1.5"	0.28 lbs.
40132	1"	1.6"	0.30 lbs.
40134	1-1/16"	1.7"	0.32 lbs.
40136	1-1/8"	1.7"	0.39 lbs.
40138	1-3/16"	1.8"	0.70 lbs.
40140	1-1/4"	1.8"	0.70 lbs.
40144A	1-1/2"	2.3"	0.70 lbs.

ASME B107.1

## 1/2" DRIVE **METRIC** SOCKETS — 6 & 12 POINT

Item No.	Size	Length	Weight	Pt.
42010M	10 mm	1.5"	0.10 lbs.	6 PT
42011M	11 mm	1.5"	0.11 lbs.	6 PT
42012M	12 mm	1.5"	0.12 lbs.	6 PT
42013M	13 mm	1.5"	0.12 lbs.	6 PT
42014M	14 mm	1.5"	0.12 lbs.	6 PT
42015M	15 mm	1.5"	0.12 lbs.	12 PT
42016M	16 mm	1.5"	0.12 lbs.	12 PT
42017M	17 mm	1.5"	0.17 lbs.	12 PT
42018M	18 mm	1.5"	0.17 lbs.	12 PT
42019M	19 mm	1.5"	0.18 lbs.	12 PT
42020M	20 mm	1.5"	0.19 lbs.	12 PT
42021M	21 mm	1.5"	0.20 lbs.	12 PT
42022M	22 mm	1.5"	0.25 lbs.	12 PT
42023M	23 mm	1.5"	0.26 lbs.	12 PT
42024M	24 mm	1.5"	0.28 lbs.	12 PT
42025M	25 mm	1.6"	0.30 lbs.	12 PT
42026M	26 mm	1.6"	0.33 lbs.	12 PT
42027M	27 mm	1.7"	0.37 lbs.	12 PT
42028M	28 mm	1.7"	0.44 lbs.	12 PT
42030M	30 mm	1.7"	0.48 lbs.	12 PT
42032M	32 mm	1.8"	0.50 lbs.	12 PT
42036M	36 mm	2.2"	0.96 lbs.	12 PT

ASME B107.5M



## 1/2" DRIVE DEEP SOCKETS — 6 POINT

Item No.	Size	Length	Weight
40416	1/2"	3.1"	0.27 lbs.
40418	9/16"	3.1"	0.29 lbs.
40420	5/8"	3.1"	0.27 lbs.
40422	11/16"	3.1"	0.32 lbs.
40424	3/4"	3.1"	0.41 lbs.
40426	13/16"	3.1"	0.42 lbs.
40428	7/8"	3.1"	0.50 lbs.
40430	15/16"	3.1"	0.54 lbs.
40432	1"	3.1"	0.62 lbs.
40434	1-1/16"	3.1"	0.76 lbs.
40436	1-1/8"	3.1"	0.79 lbs.

ASME B107.1



# Sockets & Accessories

## 1/2" DRIVE DEEP *METRIC* SOCKETS — 6 POINT

Item No.	Size	Length	Weight
45010M	10 mm	3.1"	0.23 lbs.
45011M	11 mm	3.1"	0.28 lbs.
45012M	12 mm	3.1"	0.28 lbs.
45013M	13 mm	3.1"	0.28 lbs.
45014M	14 mm	3.1"	0.28 lbs.
45015M	15 mm	3.1"	0.28 lbs.
45016M	16 mm	3.1"	0.32 lbs.
45017M	17 mm	3.1"	0.33 lbs.
45018M	18 mm	3.1"	0.36 lbs.
45019M	19 mm	3.1"	0.37 lbs.
45020M	20 mm	3.1"	0.46 lbs.
45021M	21 mm	3.1"	0.47 lbs.
45022M	22 mm	3.1"	0.51 lbs.
45023M	23 mm	3.1"	0.51 lbs.
45024M	24 mm	3.1"	0.51 lbs.
45025M	25 mm	3.1"	0.62 lbs.
45026M	26 mm	3.1"	0.63 lbs.
45027M	27 mm	3.1"	0.65 lbs.

ASME B107.5M



## 1/2" DRIVE DEEP SOCKETS — 12 POINT

Item No.	Size	Length	Weight
40316	1/2"	3.1"	0.26 lbs.
40318	9/16"	3.1"	0.26 lbs.
40320	5/8"	3.1"	0.26 lbs.
40322	11/16"	3.1"	0.33 lbs.
40324	3/4"	3.1"	0.39 lbs.
40326	13/16"	3.1"	0.40 lbs.
40328	7/8"	3.1"	0.47 lbs.
40330	15/16"	3.1"	0.56 lbs.
40332	1"	3.1"	0.58 lbs.
40334	1-1/16"	3.1"	0.71 lbs.
40336	1-1/8"	3.2"	0.72 lbs.

ASME B107.1



## 1/2" DRIVE DEEP *METRIC* SOCKETS — 12 POINT

Item No.	Size	Length	Weight
44010M	10 mm	3.1"	0.25 lbs.
44011M	11 mm	3.1"	0.31 lbs.
44012M	12 mm	3.1"	0.27 lbs.
44013M	13 mm	3.1"	0.27 lbs.
44014M	14 mm	3.1"	0.29 lbs.
44015M	15 mm	3.1"	0.25 lbs.
44016M	16 mm	3.1"	0.26 lbs.
44017M	17 mm	3.1"	0.33 lbs.
44018M	18 mm	3.1"	0.38 lbs.
44019M	19 mm	3.1"	0.41 lbs.
44020M	20 mm	3.1"	0.44 lbs.
44021M	21 mm	3.1"	0.39 lbs.
44022M	22 mm	3.1"	0.50 lbs.
44023M	23 mm	3.1"	0.56 lbs.
44024M	24 mm	3.1"	0.54 lbs.
44025M	25 mm	3.1"	0.63 lbs.
44026M	26 mm	3.1"	0.60 lbs.
44027M	27 mm	3.1"	0.55 lbs.

ASME B107.5M



# Sockets & Accessories



TS-1460

TS-2418

## 1/2" DRIVE TORX® SOCKETS

Item No.	Description	Size	Weight
TS-1460	Internal	T60	0.25 lbs.
TS-2418	External	E18	0.27 lbs.



## 1/2" DRIVE WHEEL IMPACT LUG SOCKET KIT — 6 POINT

- To remove or install most wheel lugs with a 1/2" drive impact gun.
- Kit includes a double-end socket with a 3/4" opening on one end and 13/16" on the other and a 2-5/8" long extension bar.

Item No.	Description	Weight
UW-1505	Kit (Socket and Extension)	0.91 lbs.
UW-1500	Socket Only 2.8"	0.57 lbs.
UW-30	3" Extension Only	0.28 lbs.



## 1/2" DRIVE FRONT WHEEL DRIVE DEEP SOCKET FOR GM FRONT WHEEL AXLE NUTS — 6 POINT

Item No.	Size	Length	Weight
UWP-430M	30 mm	3.5"	1.05 lbs.
UWP-436M	36 mm	3.5"	1.06 lbs.



## 1/2" DRIVE IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
UW-1612	3/8"	1.5"	0.18 lbs.
UW-1614	7/16"	1.5"	0.18 lbs.
UW-1616	1/2"	1.5"	0.19 lbs.
UW-1618	9/16"	1.5"	0.19 lbs.
UW-1620	5/8"	1.5"	0.22 lbs.
UW-1622	11/16"	1.5"	0.22 lbs.
UW-1624	3/4"	1.5"	0.26 lbs.
UW-1626	13/16"	1.6"	0.31 lbs.
UW-1628	7/8"	1.6"	0.40 lbs.
UW-1630	15/16"	1.8"	0.44 lbs.
UW-1632	1"	1.8"	0.53 lbs.
UW-1634	1-1/16"	1.8"	0.56 lbs.
UW-1636	1-1/8"	2.0"	0.66 lbs.
UW-1638	1-3/16"	2.0"	0.79 lbs.
UW-1640	1-1/4"	2.0"	0.82 lbs.

ASME B107.2

Torx® is a registered trademark of Acument Intellectual Properties, LLC



# Sockets & Accessories

## 1/2" DRIVE **METRIC** IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
UW-610M	10 mm	1.5"	0.19 lbs.
UW-611M	11 mm	1.5"	0.18 lbs.
UW-612M	12 mm	1.5"	0.19 lbs.
UW-613M	13 mm	1.5"	0.17 lbs.
UW-614M	14 mm	1.5"	0.18 lbs.
UW-615M	15 mm	1.5"	0.19 lbs.
UW-616M	16 mm	1.5"	0.20 lbs.
UW-617M	17 mm	1.5"	0.23 lbs.
UW-618M	18 mm	1.5"	0.24 lbs.
UW-619M	19 mm	1.5"	0.25 lbs.
UW-620M	20 mm	1.6"	0.29 lbs.
UW-621M	21 mm	1.6"	0.33 lbs.
UW-622M	22 mm	1.6"	0.35 lbs.
UW-624M	24 mm	1.6"	0.44 lbs.
UW-627M	27 mm	2.0"	0.59 lbs.

ASME B107.33M



## 1/2" DRIVE DEEP IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
UW-1512	3/8"	3.3"	0.38 lbs.
UW-1514	7/16"	3.3"	0.43 lbs.
UW-1516	1/2"	3.3"	0.44 lbs.
UW-1518	9/16"	3.3"	0.46 lbs.
UW-1520	5/8"	3.3"	0.46 lbs.
UW-1522	11/16"	3.3"	0.47 lbs.
UW-1524	3/4"	3.3"	0.50 lbs.
UW-1526	13/16"	3.3"	0.61 lbs.
UW-1528	7/8"	3.5"	0.72 lbs.
UW-1530	15/16"	3.5"	0.83 lbs.
UW-1532	1"	3.5"	1.02 lbs.
UW-1534	1-1/16"	3.5"	1.03 lbs.
UW-1536	1-1/8"	3.5"	1.04 lbs.

ASME B107.2




## 1/2" DRIVE **METRIC** DEEP IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
UW-510M	10 mm	3.2"	0.43 lbs.
UW-511M	11 mm	3.3"	0.43 lbs.
UW-512M	12 mm	3.3"	0.43 lbs.
UW-513M	13 mm	3.3"	0.46 lbs.
UW-514M	14 mm	3.3"	0.44 lbs.
UW-515M	15 mm	3.3"	0.40 lbs.
UW-516M	16 mm	3.3"	0.37 lbs.
UW-517M	17 mm	3.3"	0.43 lbs.
UW-518M	18 mm	3.3"	0.412 lbs.
UW-519M	19 mm	3.3"	0.48 lbs.
UW-520M	20 mm	3.3"	0.57 lbs.
UW-521M	21 mm	3.3"	0.63 lbs.
UW-522M	22 mm	3.3"	0.68 lbs.
UW-524M	24 mm	3.3"	0.71 lbs.
UW-526M	26 mm	3.5"	1.04 lbs.
UW-527M	27 mm	3.5"	1.15 lbs.

ASME B107.33M



# Sockets & Accessories



## 1/2" DRIVE IMPACT EXTENSIONS

Item No.	Size	Length	Weight
UW-30	1/2"	3"	0.28 lbs.
UW-24	1/2"	5"	0.45 lbs.
UW-25	1/2"	10"	0.99 lbs.

ASME B107.2



## 1/2" DRIVE IMPACT UNIVERSAL JOINT

- Designed to provide flexibility when working in tight restricted areas.
- Special "Ball Type Joint" gives this universal joint the added strength necessary for its rugged application.
- Black oxide finish.

Item No.	Size	Length	Weight
49976	1/2"	3"	0.57 lbs.

ASME B107.2



## 3/4" DRIVE ROUND HEAD REVERSIBLE RATCHET

- A positive-grip ratchet that gives you extra strength for turning tough nuts.
- Precision engineered, 45-tooth mechanism permits close acting operation.
- Head is 2-3/8" in diameter.

Item No.	Description	Length	Weight
69945B	45 Tooth	20.3"	5.27 lbs.
69945BR	Ratchet Renewal Kit		0.78 lbs.

ASME B107.10M



## 3/4" DRIVE HEAVY-DUTY FLEX HANDLE

Item No.	Length	Weight
69998	19"	4.20 lbs.

ASME B107.10M



## 3/4" DRIVE HEAVY-DUTY SLIDE TEE HANDLE

- For driving manually operated sockets.
- Large leverage handle for comfortable application of force.
- Movable/slidable square drive.
- Final tightening can be done with both hands.

Item No.	Length	Weight
69997	20"	3.20 lbs.

ASME B107.10M



## 3/4" DRIVE HEAVY-DUTY EXTENSIONS

Item No.	Length	Weight
69993	4"	0.87 lbs.
69995	8"	1.36 lbs.
69994	16"	2.43 lbs.

ASME B107.10M



## 3/4" DRIVE HEAVY-DUTY ADAPTERS

Item No.	Female/Male	Length	Weight
49991	3/4" to 1/2"	1.9"	0.28 lbs.

ASME B107.10M



# Sockets & Accessories

## 3/4" DRIVE REDUCING ADAPTER

• Permits use of 3/4" drive sockets with 1" drive tool.

Item No.	Female/Male	Length	Weight
69990	1" to 3/4"	3"	1.33 lbs.

ASME B107.10M



## 3/4" DRIVE HEAVY-DUTY SOCKETS — 12 POINT

Item No.	Size	Length	Weight
60026A	3/4"	2.0"	0.32 lbs.
60027A	13/16"	2.0"	0.38 lbs.
60028	7/8"	2.0"	0.42 lbs.
60030	15/16"	2.0"	0.51 lbs.
60032	1"	2.0"	0.59 lbs.
60034	1-1/16"	2.0"	0.63 lbs.
60036	1-1/8"	2.2"	0.68 lbs.
60038	1-3/16"	2.2"	0.60 lbs.
60040	1-1/4"	2.3"	0.95 lbs.
60042	1-5/16"	2.3"	0.90 lbs.
60044	1-3/8"	2.3"	0.86 lbs.
60046	1-7/16"	2.4"	1.10 lbs.
60048	1-1/2"	2.4"	1.06 lbs.
60050	1-9/16"	2.6"	1.45 lbs.
60052	1-5/8"	2.6"	1.36 lbs.
60054	1-11/16"	2.7"	1.57 lbs.
60056	1-3/4"	2.7"	1.49 lbs.
60058	1-13/16"	2.9"	1.81 lbs.
60060	1-7/8"	2.9"	1.81 lbs.
60064	2"	3.1"	2.31 lbs.
60068	2-1/8"	3.2"	2.66 lbs.
60070	2-3/16"	3.2"	2.91 lbs.
60072	2-1/4"	3.4"	3.15 lbs.
60076	2-3/8"	3.6"	3.84 lbs.

ASME B107.1



## 3/4" DRIVE **METRIC** HEAVY-DUTY SOCKETS — 12 POINT

Item No.	Size	Length	Weight
61019M	19 mm	2.0"	0.36 lbs.
61021M	21 mm	2.0"	0.37 lbs.
61022M	22 mm	2.0"	0.39 lbs.
61023M	23 mm	2.0"	0.50 lbs.
61024M	24 mm	2.0"	0.51 lbs.
61025M	25 mm	2.0"	0.53 lbs.
61026M	26 mm	2.0"	0.54 lbs.
61027M	27 mm	2.0"	0.61 lbs.
61028M	28 mm	2.2"	0.68 lbs.
61029M	29 mm	2.2"	0.69 lbs.
61030M	30 mm	2.2"	0.71 lbs.
61031M	31 mm	2.2"	0.77 lbs.
61032M	32 mm	2.2"	0.80 lbs.
61035M	35 mm	2.3"	0.86 lbs.
61036M	36 mm	2.4"	1.11 lbs.
61038M	38 mm	2.4"	1.22 lbs.
61041M	41 mm	2.6"	1.38 lbs.
61042M	42 mm	2.7"	1.81 lbs.
61046M	46 mm	2.9"	1.87 lbs.
61050M	50 mm	3.1"	2.36 lbs.
61054M	54 mm	3.2"	2.43 lbs.
61055M	55 mm	3.2"	2.58 lbs.

ASME B107.5M



# Sockets & Accessories



## 3/4" DRIVE IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
UW-2424	3/4"	1.9"	0.75 lbs.
UW-2426	13/16"	1.9"	0.75 lbs.
UW-2428	7/8"	2.0"	0.75 lbs.
UW-2430	15/16"	2.0"	0.78 lbs.
UW-2432	1"	2.1"	0.78 lbs.
UW-2434	1-1/16"	2.1"	0.78 lbs.
UW-2436	1-1/8"	2.2"	0.89 lbs.
UW-2438	1-3/16"	2.2"	1.02 lbs.
UW-2440	1-1/4"	2.2"	1.14 lbs.
UW-2442	1-5/16"	2.2"	1.25 lbs.
UW-2444	1-3/8"	2.3"	1.27 lbs.
UW-2446	1-7/16"	2.3"	1.42 lbs.
UW-2448	1-1/2"	2.4"	1.51 lbs.

ASME B107.2



## 3/4" DRIVE DEEP IMPACT SOCKETS — 6 POINT

Item No.	Size	Length	Weight
UW-2624	3/4"	3.3"	1.30 lbs.
UW-2626	13/16"	3.3"	1.30 lbs.
UW-2628	7/8"	3.3"	1.35 lbs.
UW-2630	15/16"	3.3"	1.31 lbs.
UW-2632	1"	3.3"	1.23 lbs.
UW-2634	1-1/16"	3.3"	1.17 lbs.
UW-2636	1-1/8"	3.3"	1.27 lbs.
UW-2638	1-3/16"	3.3"	1.47 lbs.
UW-2640	1-1/4"	3.3"	1.64 lbs.
UW-2642	1-5/16"	3.3"	1.78 lbs.
UW-2644	1-3/8"	3.3"	1.87 lbs.
UW-2646	1-7/16"	3.5"	2.12 lbs.
UW-2648	1-1/2"	3.5"	2.45 lbs.

ASME B107.2



## BUDD WHEEL SOCKETS — 6 POINT

- Designed for quick application and removal of Budd type wheels.
- Each socket has two openings, 13/16" square and 1-1/2" hex, eliminating the need for two separate sockets.

Item No.	Drive Size	Length	Weight
UWP-660	3/4"	4.0"	2.00 lbs.
UWP-1460	1"	4.0"	2.00 lbs.

